

Special Resistors

<i>O/Ref</i>	<i>Qty</i>	<i>Description</i>	<i>Project</i>
O MC 07-08-010	4	2x10 Ohms (+30% max) - 60MJ (3MW/40sec) in a IP44 Hot Dip Galvanized Enclosure Cooled by Hydro-cooler (10m ³ /h) - DNV Certified	<i>NCL C33 (Cruise)</i>
O MC 07-08-010	4	2x10 Ohms (+30% max) - 60MJ (3MW/40sec) in a IP44 Hot Dip Galvanized Enclosure Cooled by Hydro-cooler (10m ³ /h) - DNV Certified	<i>NCL D33 (Cruise)</i>
O MC 08-07-014	1	2x10 Ohms (+30% max) - 60MJ (3MW/40sec) in a IP44 Hot Dip Galvanized Enclosure Cooled by Hydro-cooler (10m ³ /h) - DNV Certified	<i>NCL C33 (Cruise)</i>
O MC 08-03-010	4	4x3,5 Ohms (+30% max) - 80MJ (4MW/40sec) in a IP44 RAL 7047 Painted Galvanized Enclosure Cooled by Hydro-cooler (10m ³ /h) - BV Certified	<i>TMT LNG</i>
O MC 08-03-011	4	4x3,5 Ohms (+30% max) - 80MJ (4MW/40sec) in a IP44 RAL 7047 Painted Galvanized Enclosure Cooled by Hydro-cooler (10m ³ /h) - DNV Certified	<i>Knutzen LNG</i>
O MC 08-03-012	4	4x3,5 Ohms (+30% max) - 80MJ (4MW/40sec) in a IP44 RAL 7047 Painted Galvanized Enclosure Cooled by Hydro-cooler (10m ³ /h) - ABS Certified	<i>BG LNG</i>
O MC 08-09-004	2	Three-Phase Resistor (IP23) 22kV - 350A/5sec c/w CT per Phase in a Hot Dip Galvanized Enclosur	<i>AITIK 36 / Switzerland</i>